



G1

POLYGROUT

Water resistant grout for swimming pool tile joints.

GROUT **CERAMIC TILES**

POLYGROUT is a fine colored powder which, when mixed with water, gives a smooth, easily applied creamy paste for clean grouting of ceramic tiles. It sets to a decorative water resistant finish.

DESCRIPTION

- Water-resistant (suitable for swimming pools).
- Self-colored.
- Resistant to cracking in joints up to 3mm wide.
- Ideal for internal and exterior applications.

COMPOSITION

POLYGROUT is a blend of hydrophobic cement, fillers and organic additives

STANDARDS:

- BS 5980 - Cementitious Adhesives and Grouts

APPLICATION PROCEDURES:

Allow at least 24 hours between fixing tiles and grouting. Mix grout powder with water to give a smooth, thick consistency. Leave to stand for 15 minutes before using. Apply to tile joints with a squeegee, brush or sponge. Remove surplus grout with a damp sponge. When grouting is completed, polish tiles with a dry cloth.

ADVANTAGES

Comp.Strength	> 30N / mm ²
Tensile Strength	> 2.5N / mm ²
Shrinkage	< 2mm / m

PACKAGING:

POLYGROUT is available in 10 and 20kg sacks.

STORAGE:

Store out of direct sunlight, clear of the ground on pallets protected from rain- fall. Avoid excessive compaction.

CAUTIONS:

Health and Safety:

As POLYGROUT contains Portland cement, POLYGROUT may cause irritation to skin or eyes. In case of accidental contact with eyes, immediately flush with plenty of water for at least 10 minutes and seek medical advice if necessary.

FOR MORE INFORMATION, PLEASE CONTACT PHONE NO. 00966 2 6204224



LEGAL DISCLAIMER: Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.