





# **POLYWED TILE & GROUT CLEANER**

Coverage: 1 kg covered from 3.5 to 15 m<sup>2</sup>

GROUT CLEANER

Polywed Tile & Grout Cleaner is a acidic cleaner formulated to remove cement grout haze, mortar residue, mineral deposits, ruststainsandefflorescence fromtile,concreteandmasonrysurfaces. Itis also effective for removing hardwater stains, lime deposits and soap scum.

# FEATURES AND BENEFITS

Easy to apply and can be cleaned easily. It only needs to be mixed with water available in a wide range of attractive colors (please consult our color chart board).

#### WHERE TO USE

- Formulated to remove cement grout haze, mineral deposits, lime deposits, rust stains, soap scum and mortar residue
- Concentrated formula
- Contains no phosphates

### **PRODUCT APPLICATION**

Choose all appropriate safety equipment before use... Always test first in several inconspicuous areas to confirm desired

- 1. Avoid skin and eye contact by wearing chemical-resistant gloves and protective lenses.
- 2. Shake well before using.
- 3. Workinginasmall, manageablearea of about 15 sq.ft. (1,39 m2), liberally apply an even coat over the required area with a paint brush, mop, sponge or paint pad. Do not apply with a sprayer.
- 4. Immediatelyremove productfrom unintended surfaces withawet cloth to prevent potential damage to those surfaces.
- 5. Allow product to stand on the surface for 2 to 5 minutes.
- 6. Do not let Polywed Tile & Grout Cleaner dry on the surface. Keep the surface wet by adding more product.
- 7. Agitate surface with a soft brush or white scrubpad after first testing a small area to make sure that a brush or pad will not scratch the surface
- 8. Thoroughly rinse the surface with clean water. Mop or wetvacuum up the dirty solution and allow the surface to dry thoroughly. Closecontainer tightly after each use. Store in original container only. Store between temperatures of 35°F to 90°F (2°C to 40°C).

## SHELF LIFE AND APPLICATION PROPERTIES

Shelf life	Up to 1 years when stored in the original sealed container. Freeze/ thaw-stable.
Appearance	Clear liquid
Odor	Slight odor
Physical state	Liquid
VOCs	0 g per L

### LIMITATIONS

- 1- Ensure that product does not come in contact with any nonrecommended surface. It will etch polished marble, limestone and concrete, and may lighten the color of cementitious materials.
- 2- Do not mix with other chemicals.
- 3- Do not use on acid-sensitive or polished surfaces.
- 4- Concrete and grout should be fully cured according to the manufacturer's specifications.

## **LIMITATIONS**

Sweep or vacuum all surfaces to remove loose debris. For best results, pre-wet the surface with water.

#### **PACKAGING**

Available 4 kg\*6 pic and 20 Kg















LEGAL DISCLAIMER: Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.