



# L1

## ROCKCOAT

Marble Chips Decorative Coating

### DECORATIVE COATING

ROCKCOAT is a cement based ready mixed plaster on which decorative and colored aggregates are sprayed. It has altogether the properties of a decorative and waterproof coating.

### PRIMARY USES

For interior and exterior walls. Admissible substrate: block masonry, concrete cement based plaster. Associated aggregate: marble, brick, silicate aggregate. For color and size POLYWED may propose different type: black, white, red, beige & other colors from 0.5mm to 10mm. For other aspects and samples please contact our technical department.

### CHARACTERISTICS:

ROCKCOAT is a cement based colored powder, which contains specific admix- ture, pigments and selected sand.

- Density powder: 1.36
- Grain size: 0 to 1mm.

### CONSUMPTION

For the plaster, around 1.8 m<sup>2</sup>/20 Kg bag per 1/2 mm thickness, for the aggregates, it depends on the size and the aspect required.

### PACKAGING

ROCKCOAT is packed in 20 kg bags. It can be stored for around 12 months in original packaging and dry stored condi- tions.

### PACKAGING

ROCKCOAT is packed in 20 kg bags. It can be stored for around 12 months in original packaging and dry stored condi- tions.

### INSTRUCTION OF USE

#### Substrate preparation:

Substrate must be sound, clean and dust free and free from all traces of oil, gypsum, paint or laitance. Few hours before moisten the surface, dampen the slabs one day before too, without making puddles.

#### Preparation of the product:

Mix a 20kg bag with 8 liter of water use an electric slow speed mixer for 2 or 3 minutes until an homogenous creamy paste is obtained.

#### Application of the product:

Apply the mix on the wall like a usual plas- ter with a thickness around 5 mm smooth it and then project the aggregates by using a spray gun or by a trowel. The projection may be done in one or two ways.

- Setting time depends on the temperature and humidity.
- Do not apply in strongly ventilated area or in hot weather.
- Avoid bright sunshine and temperature higher than 50C.
- We recommended the creation of joint every 15 m<sup>2</sup>.
- Order all your aggregates once in order to obtain the same aspect and color all over your project.

### CAUTIONS:

#### Health and Safety:

ROCKCOAT may cause irritation to skin or eyes. In case of accidental contact with eyes. Immediately flush with plenty of water for at least 10 minutes and seek medical advice if necessary.

#### Fire:

ROCKCOAT is non flammable.



**LEGAL DISCLAIMER:** Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.