



# L2

## PREMIXED PLASTER

A cementations ready mix plaster.

### DECORATIVE COATING

PREMIXED PLASTER is a cementations ready mix plaster. Keeping a homogeneous mix and its content in additives it allows better workability and curing. It is used in internal and external plastering works .

### SUBSTRATES

- Cast concrete.
- Pre fabricated concrete.
- Concrete blocks, bricks etc.

### ADVANTAGES

- pre-packed, easy to use only add water .
- precision made, constant result .
- shrinkage compensating .
- high build, non slump .
- excellent compressive strength .
- weather proof.

### APPLICATION

All substrates must be clean, and free dust. Mix manually mechanically a 25Kg. bags of premixed plaster to 4-5 liters clean water until homogeneous paste is obtained. Leave the mix five minutes apply by manually plastering trowel or mechanical projection machines.

### PACKAGING

Packing in 25 kg paper bag.

### STANDARDS

- 150/ASTM-C144
- C 897-96

### STORAGE

All materials should be stored under cover and clear of the ground. Protect from all sources of moisture and frost. Rotate stock in order not to exceed the shelf life of 12 months.

### CHARACTERISTICS

Appearance	Gray powder
Density	1.47+-0.01
Green size	0.02 to 2.0mm
Wet mix	< 2 hours
Initial adhesion	> 0.3 N/mm2
Bending strength	3+-1 N/mm2
Density of hardened products	1.8+-2 N/mm2
Coverage	1.5Kg/m2/1mm thickness

### PRECAUTION (HEALTH & SAFETY)

PREMIXED PLASTER is non flammable. As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn (see packaging for specific instruction). Treat any splashes to the skin or eyes with fresh water immediately. Ensure the container is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure products is stored as instructed on the safety section of the labeling.

### PRECAUTION (HEALTH & SAFETY)

provides onsite technical assistance and guidance for use of our products. For further information consult technical services.



**LEGAL DISCLAIMER:** Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.