



P5

POLYWED GLOSS ENAMELS

Oil Base Paint glossy high-quality external and internal applications

OIL BASE **GLOSSY** **EXTERNAL** **INTERNAL**

Oil base paint glossy high-quality external and internal applications, has very good properties in the stability of gloss and gives smooth surface appearance and excellent properties in coverage and characteristics, very good at resisting hard weather conditions. conformity with the standards and specifications Arabia 2002/470

BASIC USES

Final Coat in external and internal applications used on concrete surfaces ,gypsum and wood. As well as the steel surfaces .

APPLICATION INSTRUCTIONS

- Preparing the surface using sandpaper until it has remove the granules and all traces of oil, grease, dust and dirt completely from the surface.
- Clean the surface of the sanding dust by a broad soft brush or compressed air.
- A single layer of the base coating and leave it to dry.

APPLICATION TOOLS

- Roller
- Brush: Basic

PACKAGE

Pail 18 kg &1 Gallon

VALIDITY OF THE PRODUCT STORAGE

Almost 12 months in a closed container - suitable cool, dry and ventilated place

TECHNICAL DATA

Density	1.1 at a temperature ° 25 m. .ASTM D-1475+
Viscosity	90 Unit Corps at a temperature ° 25 m. .ASTM D-562
Solid content	46% by volume .ASTM D-5201
Coverage rate	10 m ² / Kg, at a dry layer thickness of 30 microns.
Scratch resistance	Passing.ASTM D-5178
Water resistance	Passing ASTM D-870
Adhesion strength	pass, .ASTM D-3359
Dryness time	Surface dry 3hours. 16 hours to complete dryness.
Diluted	Thinner .

P5

POLYWED GLOSS ENAMELS

Oil Base Paint glossy high-quality external and internal applications

SPECIAL INSTRUCTIONS

- You must paint mixing well until it becomes homogeneous before use.
- Dilution appropriate quantity using a Thinner to get the proper viscosity.
- Do not paint over wet surfaces only after fully dry drier.
- Not apply the next layer coating unless the previous layer to dry completely.
- Desired temperature 25-30 ° C, at least.
- Surface must be free of moisture and not less than 8% and moisture content of not more than 70%.

SAFETY INSTRUCTIONS

- Ensure adequate ventilation during application, avoid inhaling mist or vapors during paint.
- Paint must be out of the reach of children.
- In case of contact with the paint to the skin or eyes should be washed thoroughly with water and should avoid eating, drinking or smoking during paint

FOR MORE INFORMATION PLEASE CONTACT PHONE NO 0096626204224



LEGAL DISCLAIMER: Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.