



# T4

## FRENCH TILE ADHESIVE

TILE ADHESIVE FOR CERAMIC TILES USED FOR FLOORS AND WALLS

### ADHESIVE

The standard tile adhesive for ceramic tiles, insures continuous adhesion in residential and commercial buildings. Areas for use: Ideal for fixing all types of Ceramic Tiles. In residential and commercial buildings. Tiling on smooth concrete surfaces, lightweight bricks, blocks, plaster boards.

### APPLICATION

- For permanent fixing of all types of ceramic tiles.
- Can be used internally and externally.

### ADVANTAGES

- Ready for use, just requires the addition of water.
- good bond strength.
- Suitable for internal and external application.

### CAUTIONS

#### Health and Safety:

As contains Portland cement, may cause irritation to skin or eyes. In case of accidental contact with eyes, immediately flush with plenty of water for at least 10 minutes and seek medical advice if necessary.

#### Fire:

Is non flammable.

### CAUTIONS

#### Substrate preparation:

All surfaces must be clean and free from oil, grease or loose materials. Substrate should be dimensionally stable. Allow time for shrinkage and structural strain movements.

#### Priming

Can be applied directly on concrete, cement plaster, screed and cement or lime mortar.

#### Mixing:

5.0 liters (for each 20 kg bags) of clean water should be added to a clean container. Spread to a uniform thickness of up to 5 mm. Place tiles firmly over the applied area. Do not apply large areas of adhesives that can not be covered with in the open wet time of the adhesive.

#### Joints:

Tiles should not be placed over expansion or contraction joints. Stop tiles on joint edges and fill joints with flexible sealant.

### TYPICAL PROPERTIES

Color:	white
Mix density:	1.8±0.1
Open time:3mm thickness @ 25 °C	6 -10 min
Comp. Strength	>5 KN
Max. application Temperature:	60 C
Tensile adhesion strength :(EN 1348:1999)	>0.25

### YIELD

Approximately 5-6 m<sup>2</sup>/20kg bag at 5 mm thick- ness.

### CLEANING

All tools should be cleaned immediately after finishing with water. Hardened materials should be cleaned mechanically.

### PACKAGING

Is available in 20 kg bags.

### STORAGE

Shelf life is 12 months if stored at temperatures between 2 ° Cand 50 °C.

If these conditions are exceeded in any respect, technical department should be contacted for advice.



**LEGAL DISCLAIMER:** Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.