



Y3

WATER BASED PUTTY

READY PUTTY FINISH COAT PLASTER

WATERPROOFING **PUTTY**

Is a ready putty based for plaster, brick, stone, wood etc., before painting or other finishes. Provides a smooth finish.

APPLICATION

- Ideal filler for leveling up of walls before tile laying.
- Skimming expanded polystyrene and asbestos for easy painting.
- For filling small cracks in wood work. Defective paint work and gaps between floor boards.
- For fixing plaster board panels.

INSTRUCTION FOR USE

Surface preparation:

Surface must be dry. Remove dust and loose material prior to filling. Damp wood should be allowed to dry and decayed wood should be removed. Scratch smooth surface to give a good key.

For filling wood grains make a thin paste with more water which can be applied with a brush. POLYWED

PACKAGING

POLYWED READY PUTTY is available in 20 kg & 3.5 Kg.

STORAGE

All materials should be stored undercover and clear of the ground. Protect from all sources of moisture and frost. Rotate stock in order not to exceed the shelf life of 12 months. Wind and direct sunlight must be avoided.

CHARACTERISTICS

Aspect	Yellowish or white Slurry
Composition	Special Polymers
Mixed wet density	2.0g/cm ³
Coverage kg/m ²	2
Flexural Strength	0.5 1.2 2.36
Potlife hours	>9MPaat28days

CAUTIONS

Health and Safety:

As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn (see packaging for specific instructions). Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting, but call for medical assistance immediately. Ensure the container is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure a product is stored as instructed on the safety section of the labeling.



LEGAL DISCLAIMER: Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.