

# T5

## POLYWED READY TILE ADHESIVE

READY MIX TILE ADHESIVE IN PASTE FORM

### ADHESIVE

Tile Adhesive T5 is an economical, high quality, all-purpose acrylic adhesive for tiles and clinkers. It is ideally suited for use on exterior and interior surfaces of concrete, plasterboard, etc. Maxi Tile paste is ready-mixed and easy to apply by notched trowel.

### USES

Tile Adhesive T5 can be used on walls of fair faced concrete, lightweight concrete, plasterboard, chipboard, plywood, gypsum wall, sand and cement plasters and screeds. Maxi Tile paste is not suitable for prolonged saturation areas such as floors, swimming pools etc.

### PRODUCT INFORMATION

Composition	Styrene Acrylate and special graded fillers
Packaging	25 kg bag
Appearance / Colour	White powder
Shelf Life	12 months in original unopened container
Storage Conditions	Store properly in dry conditions, in undamaged and unopened, original sealed packaging.
Density	Wet density: ~1.22 kg/l (at +25 °C)
Maximum Grain Size	Dmax: 0.2 mm

### APPLICATION INFORMATION

Coverage	2-3 kg/m <sup>2</sup> depending on tile base.
SHELF LIFE STORAGE	Can be stored 12 months in a normal environment in original packaging in a dry elevated area.

# T5

## POLYWED READY TILE ADHESIVE

READY MIX TILE ADHESIVE IN PASTE FORM

### APPLICATION INSTRUCTION

#### SURFACE PREPARATION

- Ensure that the surface is level and all dust, dirt and foreign matter are brushed and scraped away. Also ensure the surface is solid and free from salts, oil, grease and ridges.
- All cracks, chips, voids and damages should be repaired with an appropriate filler.
- Absorbent or porous surface and plasterboards should be primed with Polywed Primer.

### APPLICATION

Apply Polywed ready tile adhesive in a layer approximately 3mm thick to the surface with the smooth side of a notched trowel. Pull the notched edge of the trowel through the applied layer. Push and twist the tiles into place so that complete adhesion is established. Fix tiles before the adhesive layer is surface dry. Plan work accordingly. Do not allow a "skin" to form on the surface of applied adhesive.

### CLEANING OF TOOLS

Clean all tools and application equipment with clean water immediately after use. Hardened / cured material can only be removed mechanically.

### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### HEALTH AND SAFETY INFORMATION

For information and advice on the safe handling storage and disposal of chemical products, users shall refer to the most recent MSDS containing all the details.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application.



**LEGAL DISCLAIMER:** Polywed endeavors to ensure that any advice, recommendations, information it may give, is accurate and correct. It cannot accept any liability either directly or indirectly arising from the use of its products, because it has no direct or continuous control over where or how its products are applied, whether or not in accordance with any advice, specification, recommendation or information given by us. Polywed has the right to change any of the specifications mentioned in the Technical data sheets upon its discretion without prior notification. Hard copies of the Technical Data sheets are printed once or twice a year, while our technical data sheets are continuously being updated as per R&D improvements and new 3rd party testing; kindly refer to our website for the latest updated of the technical Data Sheets.